

THERMIC LANCE HOLDER SPECIFICATIONS

CODE	DESCRIPTION	COUPLING	LANCE WEIGHT	OUTER DIAM.	INSERT WALL	WIRE DIAMETER
			3Metre/6Metre	mm	mm	
OXY_001_UK	17mm NB x 1.5mm SCREWED&SOCKETED LANCE	3/4" BSPT	1.25 kg/m	20.2-21.2	1.5	N/A

N.B. ALL THERMIC CUTTING LANCES ARE 6 METRES IN LENGTH AS STANDARD, HOWEVER ANY SIZE UPTO 3 METRE CAN BE MANUFACTURED

** Also in 1 metre lengths as a Stock Item

OXY LANCE HOLDER SPECIFICATIONS

CODE	DESCRIPTION	COUPLING	LANCE WEIGHT	OUTER DIAM.	TUBE WALL	WIRE DIAMETER
			3Metre/6Metre	mm	mm	
LANCE_001_UK	20mm SCREWED&SOCKETED OXY-LANCE	3/4" BSPT	4.71/9.42 Kgs	26.2-27.2	2.6	N/A

N.B. OXY-LANCES HOLDERS ARE AVAILBLE WITH OR WITHOUT BALL
VAVLE

Terminology

NB	Nominal Bore
OD	Outer Diameter
BSPT	British Standard Pipe Thread
N/A*	For use with Compression Holder - no thread required